


IZJAVA O LASTNOSTIH DECLARATION OF PERFORMANCE		20000211	Stran 53/64 Page 53/64
1.	Enotna identifikacijska oznaka tipa proizvoda: <i>Unique identification code of the product-type:</i>	Ytong P4,4-600 PSF 115 / 2500 mm	
2.	Tip, serijska ali zaporedna številka ali kateri koli drug element, na podlagi katerega je mogoče prepoznati gradbene proizvode, v skladu s členom 11 (4): <i>Type-, batch- or serial number or other marking for the identification of the construction product in accordance with Article 11 paragraph 4:</i>	CZ014054640003057	
3.	Predvidena uporaba ali predvidene vrste uporabe gradbenega proizvoda v skladu z veljavno harmonizirano tehnično specifikacijo, kot jih predvideva proizvajalec: <i>Intended use or uses defined by the manufacturer of the construction product in accordance with the applicable technical specification:</i>	Preklade za nosilne in predelne zidove Lintel for walls and partitions	
4.	Ime, registrirano trgovsko ime ali registrirana blagovna znamka in naslov proizvajalca v skladu s členom 11 (5): <i>Name, registered trade name or trade mark and contact address of the manufacturer in accordance with Article 11, paragraph 5:</i>	Xella CZ, s.r.o. Vodní 550, 664 62 Hrušovany u Brna Česká republika IČ: 64832988	
5.	Po potrebi ime ali naslov pooblaščenega zastopnika, katerega pooblastilo zajema naloge, opredeljene v členu 12 (2): <i>Name and contact address of the authorised representative, who is in charge for the tasks referred to in Article 12, paragraph 2:</i>	Xella Technologie- und Forschungsgesellschaft mbH Hohes Steinfeld 1 D-14797 Kloster – Lehnin Německo	
6.	Sistem ali sistemi ocenjevanja in preverjanja nespremenljivosti lastnosti gradbenega proizvoda, kot je določeno v Prilogi V: <i>System or systems of assessment and verification of constancy of performance of the construction product in accordance with Annex V:</i>	Sistem 3 za dodatne komponente zidovja v skladu z EN 845-2 System 3 for ancillary components for masonry in accordance with EN 845-2	
7.	Za izjavo o lastnostih glede gradbenega proizvoda, za katerega velja harmoniziran standard: <i>In case of the declaration of performance concerning a construction product covered by a harmonised standard:</i>	TZUS Praha, s.p., Prosecká 811/76a, 190 00 Praha 9, Czech Republic, identifikacijska številka 1020 je izvedel začetni pregled proizvodnje, preskuse tipa in nenehno nadzoruje kontrolo tovarniške proizvodnje v skladu c CE certifikacijsko shemo sistema 3 in je izdal potrdilo o skladnosti tovarniške kontrole. <i>TZUS Praha, s.p., Prosecká 811/76a, 190 00 Praha 9, Czech Republic, NB Nr. 1020 has performed the initial inspection of the manufacturing, type tests and continuously surveys the factory production control as part of the CE-tours in accordance with System 3 and issued the following: Certificates of conformity, Declaration of conformity.</i>	

IZJAVA O LASTNOSTIH DECLARATION OF PERFORMANCE	20000211	Stran 54/64 Page 54/64
---	-----------------	---------------------------

8.	Za izjavo o lastnostih glede gradbenega proizvoda, za katerega je bila izdana evropska tehnična ocena:	-
	<i>In case of the declaration of performance concerning a construction product with a European Technical Assessment:</i>	-

9.	Navedene lastnosti <i>Declared performance</i>		Ytong P4,4-600 PSF 115 / 2500 mm	EN 845-2: 2003
	Dimenzije <i>Dimensions</i>	Dolžina, mm <i>length, mm</i>	2500	
		Širina, mm <i>width, mm</i>	115	
		Višina, mm <i>height, mm</i>	124	
	Tolerance <i>Tolerances</i>	Dolžina, mm <i>length, mm</i>	± 15	
		Širina, Višina, mm <i>width, height, mm</i>	± 5	
		Ravnost, %, mm <i>flatness, %, mm</i>	0,5%, max 10 mm	
	Oblika in rokovalje <i>Form and shape</i>	osnovne oblike regular shaped		
	Nosilnost, kN <i>Load carrying capacity, kN</i>	NPD		
	Upogib pod obremenitvijo <i>Deflection under load</i>	NPD		
	Masa na enoto dolžine, kg/m ² <i>Mass applied to length, kg/m²</i>	102		
	Toplotna prevodnost $\lambda_{10,dry}$, W/(m.K) <i>Thermal conductivity $\lambda_{10,dry}$, W/(m.K)</i>	0,160 (P=50%)		
	Reakcija na ogenj <i>Reaction to fire</i>	eurorazred A1 <i>euroclass A1</i>		
	Požarna odpornost <i>Fire resistance</i>	R 60		
	Vpijanje vode <i>Water absorption</i>	ne sme se uporabljati nezaščiten <i>not to be left exposed</i>		
	Paroprepustnost <i>Water vapour permeability</i>	5 / 15		
Trajnost pred korozijo <i>Durability against corrosion</i>	G			
<i>Durability against freeze thaw</i>	ne sme se uporabljati nezaščiten <i>not to be left exposed</i>			
Nevarne snovi <i>Dangerous substances</i>				

10.	Lastnosti proizvoda, navedenega v točki 1 in 2, so v skladu z navedenimi lastnostmi iz točke 9. Za izdajo te izjave o lastnostih je odgovoren izključno proizvajalec, naveden v točki 4. Podpisal za in v imenu proizvajalca.	 Andreas Rähse, CTO Xella Eastern Europe
	<i>The performance of the product referring to paragraph 1 and 2 correspond to the declared performance at paragraph 9. This declaration of performance was issued under the sole responsibility of the manufacturer specified in paragraph 4. Signed on behalf of the manufacturer</i>	Hrušovany u Brna, 30.6.2013