

## DECLARATION OF PERFORMANCE No 06CPR/BIII/RO/01

1. Unique identification code of the product-type : **06/BIII/GL/RO**

2. Type, batch or serial number or any other element showing identification of the construction product as required pursuant to Article 11(4).

**Dry-pressed ceramic tiles of water absorption  $E \leq 10\%$ ; Group BIII GL – according to the description on the packaging.**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Dry- pressed ceramic tiles, glazed (GL) to be used for walls inside the buildings.**

4. Name, registered trade name or registered trademark and the contact address of the manufacturer as required pursuant to Article 11(4) : **ROVESE S.A.; AL. Solidarności 36; 25-323 Kielce**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 11(5): **not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **SYSTEM 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard: **EN 14411:2012.**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **not applicable.**

9. Declared performance

| Essential characteristics               | Performance (level and/or class) | Harmonized technical specification  |
|---|----------------------------------|-------------------------------------|
| <b>Reaction to fire</b>                 | A1                               | Classified without testing(CWT)     |
| <b>Release of dangerous substances</b>  |                                  | EN 14411:2012                       |
| - Cd(Cadmium)                           | max 0,07mg/dm <sup>2</sup>       |                                     |
| - Pb(Lead)                              | max 0,8mg/dm <sup>2</sup>        |                                     |
| <b>Adhesion</b>                         | NPD                              | EN 12004:2007+A1:2012<br>EN 1015-12 |
| <b>Breaking strength:</b>               |                                  | EN 14411:2012                       |
| thickness $\geq 7,5$ mm                 | $\geq 600$ N                     |                                     |
| thickness $< 7,5$ mm                    | $\geq 200$ N                     |                                     |
| <b>Thermal shock resistance</b>         | odporne                          | EN 14411:2012                       |
| <b>Durability for:</b>                  |                                  | EN 14411:2012                       |
| - internal use                          | Pass                             |                                     |
| - external use: Freeze –thaw resistance | Not resistant                    |                                     |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Kielce 26.06.2013  
(place and date of issue)

**WICEPREZES ZARZĄDU**

**Ireneusz Kazimierski**  
(signature)