

## DECLARATION OF PERFORMANCE No 07CPR/Bib/RO/01

1. Unique identification code of the product-type : **07/Bib/UGL/RO**

2. Type, batch or serial number or any other element showing identification of the construction product as required pursuant to Article 11(4).

**Dry-pressed ceramic tiles of water absorption  $0,5\% < E \leq 3\%$ ; Group Bib UGL – according to the description on the packaging.**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Dry- pressed ceramic clinker tiles, unglazed (UGL) to be used for walls and floors inside and outside the buildings.**

4. Name, registered trade name or registered trademark and the contact address of the manufacturer as required pursuant to Article 11(4) : **ROVESE S.A.; AL. Solidarności 36; 25-323 Kielce**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 11(5): **not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **SYSTEM 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard: **EN 14411:2012.**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **not applicable.**

9. Declared performance

Essential characteristics	Performance (level and/or class)	Harmonized technical specification
<b>Reaction to fire</b>	A1 <sub>FL</sub>	Classified without testing(CWT)
<b>Adhesion</b>	NPD	EN 12004:2007+A1:2012 EN 1015-12
<b>Breaking strength:</b>		
thickness $\geq 7,5\text{mm}$	$\geq 1100\text{N}$	EN 14411:2012
thickness $< 7,5\text{mm}$	$\geq 700\text{N}$	
<b>Slipperiness</b>	According to declaration on the packaging	DIN 51130:2010
<b>Thermal shock resistance</b>	Pass	EN 14411:2012
<b>Durability for:</b>		
- internal use	Pass	EN 14411:2012
- external use: Freeze –thaw resistance	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Kielce 26.06.2013  
(place and date of issue)

**WICEPREZES ZARZĄDU**

**Ireneusz Kazimierski**  
(signature)